

Anker A1728

Anker SOLIX C300X DC Portable Power Station

288Wh | 300W

InfiniPower™



Highlights

InfiniPower™ 10 Years of Everyday Use

LiFePO4 batteries offer a 6x longer lifespan than the average power station. Designed for a decade of daily use, with an industry-leading 5-year device warranty

Ultra Portable Design

The power station features a short strap design, weighs just 2.8KG, and is 30% smaller than the industry average in the same capacity, significantly making outdoor activities easier!

Appliances Compact and Powerful in One

Equipped with a total 300W output and a 90,000 mAh (288Wh) battery, this unit features 7 ports (2 USB-A, 4 USB-C and car socket), allowing you to power multiple essential devices and tablets on the go.

Worry-Free Outdoor day and night

Pair up with 100W solar panels to recharge during the day, and enjoy nighttime activities with the built-in stretchable camping light, while also charging your essential devices.

140W Two-Way Fast Charging

Use the dual 140W PD 3.1 USB-C to power up two 16" Macbook Pros from 0% to 50% in just 40 minutes. Can recharge this power station to 100% within 70 minutes with ports as well.

Specifications

Product Model

PN	A1728
Model Name	Anker SOLIX C300X DC Portable Power Station

Battery Info

Type of Battery	LiFePO4
Capacity	288Wh
Capacity	90000mAh
Cycle Life	3000+ (to 80%)



Specifications

Power Outputs

Maximum Output	300W
----------------	------

# of Output Ports	7
-------------------	---

# of Standard AC Socket	No
-------------------------	----

AC Rated Power	No
----------------	----

AC Surge Power	No
----------------	----

AC Auto Shut-Off	-
------------------	---

# of USB-A Output	2
-------------------	---

USB-A Rated Power (per port)	5V=2.4A (12W Max)
------------------------------	-------------------

USB-A Total Output	24W
--------------------	-----

# of USB-C Output	4
-------------------	---

USB-C Rated Power (per port)	5V=3A (15W) 5V=3A/ 9V=3A/15V=3A/ 20V=3A/28V=5A (140W Max) 5V=3A/ 9V=3A/15V=3A/ 20V=5A (100W Max) 5V=3A/ 9V=3A/15V=3A/ 20V=3A/28V=5A (140W Max)
------------------------------	--

USB auto shut-off	Yes
-------------------	-----

# of Car Outlet	1
-----------------	---

Car Outlet Rated Power (per port)	10.8~14V=10A (120W Max)
-----------------------------------	-------------------------

Specifications

Power Inputs

Input Voltage	-	EST DC Adapter Recharge Time :	No
Total Input Power	280W (2*140W USBC)	DC Input Size	XT-60
EST Recharge Time	PD : 142mins(140W) 70mins (280W)	Solar Input Power	11-28V== 8.2A(100W Max)
Use Ports While Recharging	Yes	EST Solar Recharge Time	3.2 Hours(1*100W)
Direct AC Input	No	Solar Panel Compatible	Yes
Maximum AC Input Power	No	MPPT Support	Yes
# of DC Input	1 (XT-60)		
DC Adapter	No		

Sales Market: US/CA/JP/EU/UK/DE/MEA/ANZ

Specifications

Illumination Information

Flash Light	-
Flash Light Mode	-
Ambient Light	Yes
Ambient Light Mode	Ambient Light Mode (3 Level) SOS Mode

Safety Information

Operation Temperature (°C/°F)	Charging: -20 -40°C / -4 -104°F Recharging: 0-40°C / 32-104°F
Overload Protection (AC)	-
Over-current Protection (USB-A)	>3A
Over-current Protection (USB-C)	>6A
Over-current Protection (Car Port)	>12.8A

Package Content

AC Adapter	-
Cable	140W C-C Cable 60cm

Weight & Dimension

Product Dimension	124*120*200mm 4.9x4.7x7.9In
Product Weight	2.8 kg ; 6.2 lb